


首 页 关于公司  自主开发 应用方案 下载中心 条码



条码产品

点击咨询
免费通话

意大利Datalogic条码扫描器 > Datalogic Heron G条码扫描器

- 条码扫描器
 - 美国intermec
 - 美国Symbol
 - 意大利Datalogic
 - 台湾Gyoung
 - 美国HHP (honeywell)
 - 日本Opticon
 - 美国Microscan
 - 美国Metrologic
 - 台湾IMC
 - 美国PSC
 - 新大陆nls
 - 日本东研tohken
- 条码打印机
 - 美国Intermec
 - 日本Toshiba-Tec
 - 美国斑马Zebra
 - 日本佐藤Sato
 - 日本Ring
 - 美国Datamax
 - 台湾Godex
 - 台湾TSC
 - 日本西铁城Citizen
 - 日本新盛shinsei
 - 德国CAB
 - 美国科立得Cognitive
- 数据采集终端
 - 美国intermec
 - 美国Symbol
 - 日本Casio
 - 美国Metrologic
 - 台湾Gyoung

关闭



Datalogic Heron G CCD Bar Code Scanner

The Datalogic Heron G CCD bar code scanner was developed to provide a result in a gun shaped handheld CCD bar code scanner that is characterized by its simplicity of use and ergonomics make it suitable for light retail applications. The Datalogic Heron G CCD bar code scanner is based on Datalogic's close range bar code scanning technology in light retail applications. The scanner utilizes the Datalogic patented "green spot" providing good readability especially useful in noisy environments.

The Datalogic Heron G CCD bar code scanner is available in a single interface model (Wedge), and provides flexibility and full compatibility with various interface cables.

The Datalogic Heron G CCD bar code scanner as well as all Datalogic scanners undergo rigorous tests to assure that it can withstand daily use in standard operating conditions. Research departments and quality assurance laboratories result in a scanner that meets all the requested quality standards in the market.

In addition, Datalogic Heron G CCD bar code scanner reads Reduced Size Code 39, which can be printed on smaller labels, meeting emerging market needs.

Features

- Datalogic "Green Spot"
- Single multi-interface model: USB, RS232, Wedge
- Rugged and reliable
- RSS-14 decoding capability
- Sunrise 2005 Compliant
- 5 Year Manufacturers Warranty

技术参数

日本keyence
 福建新大陆
 美国双成
 韩国蓝鸟bluebird
 韩国M3

- 无线局域网
- 美国intermec
- 美国Symbol
- 不干胶标签
- 激光打印标签
- 条码碳带
- IMC系列碳带
- 标准腊基碳带
- 混合基碳带
- 树脂基碳带
- 水洗布专用树脂碳带
- 条码打印软件
- 条码检测仪
- 条码打印机配件

Electrical Characteristics	
Humidity:	0 to 90% non condensing
Drop Resistance:	Resists repeated drops from 1.8
Storage Temp.:	-20 ° C to 70 ° C
Ambient Light Conditions:	Up to 100,000 lux
Operating Temp.:	0 ° C to 55 ° C
Protection Class:	IP30
Consumption:	Max. 180 mA / Operating 155 mA /
Power Supply:	5VDC ±5%, directly from the PC
Mechanical Characteristics	
Cable Length:	6 feet
Case Material:	ABS and Polycarbonate, co-moldec
Weight:	195 g. without cable
Dimensions:	173 x 92 x 71 mm
Performance	
Reading Indicators:	LED, Good read spot, Beeper
Programming Method:	Manual Reading special bar codes (with RS232), DLSm@rtSet? Window
Interfaces:	USB, Keyboard Wedge, RS-232
Sensor:	CCD solid state (2048 pixels)
Scanning Speed:	256 scans/sec
Warranty Period:	5 years
Light Source:	640 nm visible red LED
Reading Angle:	Pitch ± 75° ; Skew ± 70° ; Rot
Bar Codes Read:	RSS, 2/5 family, Code 39 (più Cc 128, ISBT 128, Code 93, Code 11, Delta IBM, Code 16K, Code 49
Reading Field:	0-23 cm (approx. 9 inches)
Max. Resolution:	0.1 mm

条码业界新闻 | 网站地图 | 条码行业动态

版权所有(C) 2002-2011 上海全亨科技

地址: 上海市浦东大道1097号15号楼4E室 邮编: 200135 邮箱: mail#i

电话: 021-51088451 51088452 传真: 021-50935062

