



 **条码产品**



关闭

意大利Datalogic条码扫描器 > Datalogic Magellan 9500条码扫描器

- 条码扫描器
 - 美国intermec
 - 美国Symbol
 - 意大利Datalogic
 - 台湾Gyoung
 - 美国HHP (honeywell)
 - 日本Opticon
 - 美国Microscan
 - 美国Metrologic
 - 台湾IMC
 - 美国PSC
 - 新大陆nls
 - 日本东研tohken
- 条码打印机
 - 美国Intermec
 - 日本Toshiba-Tec
 - 美国斑马Zebra
 - 日本佐藤Sato
 - 日本Ring
 - 美国Datamax
 - 台湾Godex
 - 台湾TSC
 - 日本西铁城Citizen
 - 日本新盛shinsei
 - 德国CAB
 - 美国科立得Cognitive
- 数据采集终端
 - 美国intermec
 - 美国Symbol
 - 日本Casio
 - 美国Metrologic
 - 台湾Gyoung



Datalogic Magellan 9500激光条码扫描平台

Magellan 9500 with Integrated EAS Deactivation Utilizing the Du

The Magellan 9500 Dual Antenna, with integrated Sensormatic EAS point-of-sale scanner in the world. It is the first scanner ever tags. Datalogic's innovative SurroundScan 3D Scanning technology bar code on all six sides of an item, maximizes POS throughput. shrink by providing a larger platform for weighing long and bag for all high-volume retail point-of-sale applications with Sens

OmegaTek Productivity Technology
 Datalogic Scanning SmartSentry firmware interfaces with the Sen Deactivation
 Dual EAS Antennas in the Vertical and Horizontal plane (models SurroundScan 3D Scanning Technology
 Enhanced All-Weighs scale platter
 Flash ROM for easy, low cost software upgrades
 Multiple POS interfaces support all popular host systems
 FirstStrike Advanced Decoding Software
 Powered auxiliary RS-232 port for handheld scanner
 Sunrise 2005 and GTIN compliant
 Optional Value Added Software Features: Host Download , Diagnosti (PIR) , Cashier Training / Ergonomic Index

MECHANICAL

Dimensions

Length
 Model 9502 (scanner/scale): 20.0"/ 50.8 cm
 Model 9501(scanner): 20.0"/ 50.8 cm
 Model 9503 (scanner): 20.0" / 50.8 cm
 Model 9504 (scanner/scale): 20.0" / 50.8 cm

日本keyence

福建新大陆

美国双成

韩国蓝鸟bluebird

韩国M3

- 无线局域网
- 美国intermec
- 美国Symbol

- 不干胶标签
- 激光打印标签

- 条码碳带
- IMC系列碳带

标准腊基碳带

混合基碳带

树脂基碳带

水洗布专用树脂碳带

- 条码打印软件
- 条码检测仪
- 条码打印机配件

Width: 11.5" / 29.2 cm

Depth (below counter): 6.5" / 16.5 cm

Height (above counter): 7.0" / 17.8 cm

Weight

Model 9502 (scanner/scale): 28.9 lb / 13.11 kg

Model 9501 (scanner): 22.2 lb / 10.07 kg

Model 9503 (scanner): 24.2 lb / 10.9 kg

Model 9504 (scanner/scale): 32.9 lb / 14.9 kg

Scale Capacities

Capacity: 30.0 lb / 9.99 kg or 15 kg (interface dependent)

Minimum Increment: .01 lb / 0.005 kg

Vibration Immunity: 4 programmable filter settings

Maximum Static Weight: 150 lb / 68 kg

Adjustments Required: Calibration only

DECODING CAPABILITY

The Magellan 9500 decodes and autodiscriminates all of the following
UPC Versions A & E

UPC Supplementals (Bookland & Coupon Code)

UPC Add-ons (sub 2 or P2, sub 5 or P5 & C128)

GS1 DataBar (Omnidirectional, Expanded and Stacked)

EAN 8, 13

JAN 8, 13

EAN/JAN two label

UCC/EAN 128

Code 39 (with full ASCII)

Code 128

Code 93

Interleaved 2 of 5

Italian Pharmacode

Codabar/NW7

MSI Plessey

OPTICAL

Scan Lines: 64

Motor Speed: 6,000 rpm

Scan Rate: 6,400 lines/sec.

Scan Zone: 360° x 2

Sides Read: 6

Read Height: 5.5" / 13.9 cm

ENVIRONMENTAL

Temperature Rating:

Operating: 50° to 104° F / 10° to 40° C

Storage/Transport: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

ELECTRICAL

AC Power Requirements:

Nominal: 100-250 VAC, 50-60 Hz; 9 Watts

Sleep Mode: 17 Watts (maximum) 4 Watts

COMMUNICATIONS

Host: All Magellan 9500 models support IBM RS-485, RS-232, IBM

Other: RS-232 handheld scanner port; scale host port; remote sc

SAFETY & REGULATORY

Electrical: UL 60950; CSA 60950; EN60950

Emissions: FCC part 15 subpart j, Class B (USA); AS/NZS 3548 (A
55022; CISPR 22 and others.

Laser Safety: Class IIa Laser Product; IEC 60825 Class 1 (CAUTI

Restriction of Hazardous Substances: Complies to EU RoHS

Weights & Measures: Standards - HB44, EN45501, 90/384/EEC, NOM,
Mexico, Europe, and most of the world.

[条码业界新闻](#) | [网站地图](#) | [条码行业动态](#)

版权所有(C) 2002-2011 上海全亨科技

地址: 上海市浦东大道1097号15号楼4E室 邮编: 200135 邮箱: mail#i

电话: 021-51088451 51088452 传真: 021-50935062

