



- 条码产品**
- 条码扫描器
    - 美国intermec
    - 美国Symbol
    - 意大利Datalogic
    - 台湾Gyoung
    - 美国HHP (honeywell)
    - 日本Opticon
    - 美国Microscan
    - 美国Metrologic
    - 台湾IMC
    - 美国PSC
    - 新大陆nls
    - 日本东研tohken
  - 条码打印机
    - 美国Intermec
    - 日本Toshiba-Tec
    - 美国斑马Zebra
    - 日本佐藤Sato
    - 日本Ring
    - 美国Datamax
    - 台湾Godex
    - 台湾TSC
    - 日本西铁城Citizen
    - 日本新盛shinsei
    - 德国CAB
    - 美国科立得Cognitive
  - 数据采集终端
    - 美国intermec
    - 美国Symbol
    - 日本Casio
    - 美国Metrologic
    - 台湾Gyoung
    - 日本keyence
    - 福建新大陆
    - 美国双成
    - 韩国蓝鸟bluebird
    - 韩国M3
  - 无线局域网
    - 美国intermec
    - 美国Symbol
  - 不干胶标签
  - 激光打印标签
  - 条码碳带
    - IMC系列碳带
    - 标准腊基碳带
    - 混合基碳带
    - 树脂基碳带
    - 水洗布专用树脂碳带
  - 条码打印软件
  - 条码检测仪
  - 条码打印机配件

美国Intermec条码扫描器 > Intermec SR61B条码扫描器



**Intermec SR61B Handheld Scanner**

Intermec's SR61B incorporates industry-standard Bluetooth radio technology into a cordless handheld scanner perfect for stand-alone wireless data collection interfacing to Bluetooth-enabled hosts in rugged, industrial environments. The SR61B is available with linear imaging, area imaging, MEMS-based laser, or the unparalleled near/far area imaging.

**Features**

Interfaces with Intermec terminals and personal computers  
 Choice of linear imager, area imager, or standard range laser scan options  
 Easy configuration and personalization  
 Industrial durability stands up to harsh environments

**Environment**

Operating Temperature :-20° C to +50° C (-4° F to +122° F)  
 Storage Temperature :-40° C to +70° C (-90° F to +158° F)  
 Recharging Temperature :0° C to +35° C (32° F to +95° F)  
 Humidity :0 to 95% RH, Non-condensing  
 Vibration and Shock protection :SAE Specification J1399 Class 3 (off road vehicle)  
 Environmental Protection :IP54  
 Drop Survival :26 drops onto concrete or steel surface from a height of 1.98 meters (6.5 feet)  
 Ambient light :Works in any lighting conditions from 0 to 100,000 lux

**Physical Characteristics**

Length :17.78 cm (7 in)  
 Width :6.99 cm (2.75 in)  
 Depth :11.43 cm (4.5 in)  
 Weight :  
 (Cordless version with battery):425 gm (15 oz)  
 (Cabled version without cable):280 gm (10 oz)

**Power**

Battery type/Supply :(Cordless) Lithium-ion  
 Battery Life :(Cordless) 10+ hours per full charge  
 Recharging Time :(Cordless) 2.5 hours for 90% charge  
 Cables :Cabled versions are powered via host or universal 5 volt power supply

[条码业界新闻](#) | [网站地图](#) | [条码行业动态](#)

版权所有(C) 2002-2011 上海全亨科技

地址: 上海市浦东大道1097号15号楼4E室 邮编: 200135 邮箱: mail#intermeccorp.com

电话: 021-51088451 51088452 传真: 021-50935062

