



首 页 关于公司 条码产品 自主开发 应用方案 下载中心 条码

条码产品	韩国Woosim条码打印机 > Woosim PORTI-SB50条码打印机																		
- 条码扫描器 - 美国intermec - 美国Symbol - 意大利Datalogic - 台湾Gyoung - 美国HHP (honeywell) - 日本Opticon - 美国Microscan - 美国Metrologic - 台湾IMC - 美国PSC - 新大陆nls - 日本东研tohken - 条码打印机 - 美国Intermec - 日本Toshiba-Tec - 美国斑马Zebra - 日本佐藤Sato - 日本Ring - 美国Datamax - 台湾Godex - 台湾TSC - 日本西铁城Citizen - 日本新盛shinsei - 德国CAB - 美国科立得Cognitive - 数据采集终端 - 美国intermec - 美国Symbol - 日本Casio - 美国Metrologic - 台湾Gyoung	Woosim PORTI-SB50 条码打印机 Features Pocket size (78 x 131.5 x 55mm) Light weight(200g) for true mobility Very silent printing thru direct thermal printing method High speed (50mm/sec, MAX) High resolution (203dpi:8dots/mm) HPIR, IrDA (Physical layer), UART Interface Support text and graphic printing Support bit-image(logo) download Easier paper roll loading by CLAMSHELL design Easier maintenance with self-diagnostics Free fall: 1 meter onto concrete (option 1.5 meter) Microsoft Windows ME / XP / 2000 / VISTA OS compatible Specification <table data-bbox="686 1646 1449 2072"> <thead> <tr> <th>Item</th><th>Specification</th></tr> </thead> <tbody> <tr> <td>Printing method</td><td>Direct thermal line printing</td></tr> <tr> <td>Characters per line</td><td>42cpl (MAX)</td></tr> <tr> <td>Optional Characters</td><td>Simplified/Traditional Chinese, Arabic Persian, Latin9 and Others upon request</td></tr> <tr> <td>Character size</td><td>Eng. : 9x24dots, 12x24dots Kor. : 16x24dots [24x24dots]</td></tr> <tr> <td>Resolution</td><td>203dpi, 8dots/mm</td></tr> <tr> <td>Print width</td><td>2-inch (48mm, 384dots)</td></tr> <tr> <td>Printing speed</td><td>50mm/sec (MAX)</td></tr> <tr> <td>Dimensions</td><td>78 x 131.5 x 55mm</td></tr> </tbody> </table>	Item	Specification	Printing method	Direct thermal line printing	Characters per line	42cpl (MAX)	Optional Characters	Simplified/Traditional Chinese, Arabic Persian, Latin9 and Others upon request	Character size	Eng. : 9x24dots, 12x24dots Kor. : 16x24dots [24x24dots]	Resolution	203dpi, 8dots/mm	Print width	2-inch (48mm, 384dots)	Printing speed	50mm/sec (MAX)	Dimensions	78 x 131.5 x 55mm
Item	Specification																		
Printing method	Direct thermal line printing																		
Characters per line	42cpl (MAX)																		
Optional Characters	Simplified/Traditional Chinese, Arabic Persian, Latin9 and Others upon request																		
Character size	Eng. : 9x24dots, 12x24dots Kor. : 16x24dots [24x24dots]																		
Resolution	203dpi, 8dots/mm																		
Print width	2-inch (48mm, 384dots)																		
Printing speed	50mm/sec (MAX)																		
Dimensions	78 x 131.5 x 55mm																		

日本keyence	Weight	200g (except Dry cell)
福建新大陆	Interface	HPIR, IrDA (Physical layer), UART
美国双成	Paper supplied	Thermal roll paper (57mm wide, 50?)
韩国蓝鸟bluebird	Barcode	PDF417 (2-dimension), Code128, Code39,
韩国M3	Black mark	Support black mark detection
▪ 无线局域网	Receive buffer size	10K bytes
美国intermec	Battery	Dry cell (AA size, 4EA)
美国Symbol	Battery charger	(It is recommended that a high capacit
▪ 不干胶标签	Operating temperature	Output (9VDC/800mA)
▪ 激光打印标签	Storage temperature	-10° C~50° C
▪ 条码碳带	MCBF (Mean Cycle Between	-10° C~70° C
IMC系列碳带	failure)	Mechanical
标准腊基碳带		Head
混合基碳带		37,000,000 lin
树脂基碳带		Approximately
水洗布专用树脂碳带		
▪ 条码打印软件		
▪ 条码检测仪		
▪ 条码打印机配件		

[条码业界新闻](#) | [网站地图](#) | [条码行业动态](#)

版权所有 (C) 2002—2011 上海全亨科技

地址: 上海市浦东大道1097号15号楼4E室 邮编: 200135 邮箱: mail#i

电话: 021-51088451 51088452 传真: 021-50935062

