



首 页 关于公司 条码产品 自主开发 应用方案 下载中心 条码

 条码产品	 韩国Woosim条码打印机 > Woosim PORTI-SC30条码打印机										
- 条码扫描器 - 美国intermec - 美国Symbol - 意大利Datalogic - 台湾Gyoung - 美国HHP (honeywell) - 日本Opticon - 美国Microscan - 美国Metrologic - 台湾IMC - 美国PSC - 新大陆nls - 日本东研tohken - 条码打印机 - 美国Intermec - 日本Toshiba-Tec - 美国斑马Zebra - 日本佐藤Sato - 日本Ring - 美国Datamax - 台湾Godex - 台湾TSC - 日本西铁城Citizen - 日本新盛shinsei - 德国CAB - 美国科立得Cognitive - 数据采集终端 - 美国intermec - 美国Symbol - 日本Casio - 美国Metrologic - 台湾Gyoung	Woosim PORTI-SC30 条码打印机 Features - Pocket size (75.5 x 112 x 34mm) - Light weight(224g) for true mobility - Very silent printing thru direct thermal printing method - High speed (80mm/sec, MAX) - High resolution (203dpi:8dots/mm) - UART or TTL, Bluetooth Ver2.0 interface - IrDA Ver1.0(SIR) (optional), USB(optional) interface - Support text and grahpic printing - MSR : ISO/IEC 7810, ISO/IEC 7811 (1/2 Track or 2/3 Track) - Support bit-image(logo) download - Easier paper rollloading by CLAMSHELL design - Easier maintenance with self-diagnostics - Using Combined with CDMA phone or PDA - Free fall: 1 meter onto concrete (option 1.5 meter) - Microsoft Windows ME / XP / 2000 / VISTA OS compatible Specification <table> <tr> <th>Item</th><th>Specification</th></tr> <tr> <td>Printing</td><td>Direct thermal printing</td></tr> <tr> <td>Characters per line</td><td>42cpl</td></tr> <tr> <td>Optional Characters</td><td>Simplified/Traditional Chinese, Arabic Persian, Latin9 and Others upon reques</td></tr> <tr> <td>Character size</td><td>Eng. : 9x24dots, 12x24dots Kor. : 16x24dots [24x24dots]</td></tr> </table>	Item	Specification	Printing	Direct thermal printing	Characters per line	42cpl	Optional Characters	Simplified/Traditional Chinese, Arabic Persian, Latin9 and Others upon reques	Character size	Eng. : 9x24dots, 12x24dots Kor. : 16x24dots [24x24dots]
Item	Specification										
Printing	Direct thermal printing										
Characters per line	42cpl										
Optional Characters	Simplified/Traditional Chinese, Arabic Persian, Latin9 and Others upon reques										
Character size	Eng. : 9x24dots, 12x24dots Kor. : 16x24dots [24x24dots]										

日本keyence	Resolution	203dpi, 8dots/mm
福建新大陆	Print width	2-inch (48mm, 384dots)
美国双成	Printing speed	80 mm/sec (MAX)
韩国蓝鸟bluebird	Dimensions (WxDxH)	75.5 x 112 x 34mm
韩国M3	Weight	224g
▪ 无线局域网	Interface	UART or TTL, Bluetooth Ver2.0
美国intermec		IrDA Ver1.0(SIR) [optional],
美国Symbol		USB [optional]
▪ 不干胶标签	MSR	ISO/IEC 7810, ISO/IEC 7811
▪ 激光打印标签		(1/2 Track or 2/3 Track)
▪ 条码碳带	Paper supplied	Thermal roll paper,
IMC系列碳带		label roll (57mm wide, 30?)
标准腊基碳带	Barcode	1-dimension : Code128, EAN 128, Code39
混合基碳带		2-dimension : PDF417, QR Code, DATA Ma
树脂基碳带	Black mark	Support black mark detection
水洗布专用树脂碳带	H/W Spec.	MCU : 32 bit RISC, FLASH : 4M bytes, R
▪ 条码打印软件	Receive buffer size	1M bytes
▪ 条码检测仪	Battery	Rechargeable 7.4V DC 1,200mAh (Li-ion)
▪ 条码打印机配件	Battery duration	1 hour continuous printing
	AC adapter	Input (100~250V AC, 50~60Hz)
		Output (8.4V DC / 0.8A), 4 hours full
	Operating temperature	-10° C~50° C
	Storage temperature	-10° C~70° C
	MCBF(Mean Cycle Between	Mechanical
	failure)	Head
		37,000,00
		Approxima

条码业界新闻 | 网站地图 | 条码行业动态

版权所有(C) 2002—2011 上海全亨科技

地址: 上海市浦东大道1097号15号楼4E室 邮编: 200135 邮箱: mail#i

电话: 021-51088451 51088452 传真: 021-50935062

