



全国统一服务热线

400-11

首 页 关于公司 条码产品 自主开发 应用方案 下载中心 条码

 条码产品	 韩国Woosim条码打印机 > Woosim PORTI-SD40条码打印机																				
- 条码扫描器 - 美国intermec - 美国Symbol - 意大利Datalogic - 台湾Gyound - 美国HHP (honeywell) - 日本Opticon - 美国Microscan - 美国Metrologic - 台湾IMC - 美国PSC - 新大陆nls - 日本东研tohken - 条码打印机 - 美国Intermec - 日本Toshiba-Tec - 美国斑马Zebra - 日本佐藤Sato - 日本Ring - 美国Datamax - 台湾Godex - 台湾TSC - 日本西铁城Citizen - 日本新盛shinsei - 德国CAB - 美国科立得Cognitive - 数据采集终端 - 美国intermec - 美国Symbol - 日本Casio - 美国Metrologic - 台湾Gyound	 Woosim PORTI-SD40 条码打印机 Features Pocket size (97 x 109 x 44.7mm) Light weight(350g) for true mobility Serial Impact DOT Matrix 40Columns (180dots/line) 50mm Wide Paper Width Battery Indicator UART or TTL, Bluetooth Ver2.0 Interface Support text and graphic printing Easier maintenance with self-diagnostics Free fall: 1 meter onto concrete (option 1.5 meter) Microsoft Windows ME / XP / 2000 / VISTA OS compatible Specification <table> <thead> <tr> <th>Item</th><th>Specification</th></tr> </thead> <tbody> <tr> <td>Printing Method</td><td>Serial Impact DOT Matrix system</td></tr> <tr> <td>Printing direction</td><td>Uni-directional printing</td></tr> <tr> <td>Inking</td><td>Dedication ink ribbon cartridge (black (4+0.5)×8 Font, 40columns</td></tr> <tr> <td>Character size</td><td>[6×8, 7×10, 8×8, 8×9, 10×12]</td></tr> <tr> <td>Optional Characters</td><td>Simplified/Traditional Chinese, Arabic Persian, Latin9 and Others upon reques</td></tr> <tr> <td>Characters per line</td><td>40columns (4x8 Font)</td></tr> <tr> <td>Paper width</td><td>46.8mm, 180dots/line</td></tr> <tr> <td>Print feed pitch</td><td>3.52mm (10dot lines)</td></tr> <tr> <td></td><td>57.5mm,</td></tr> </tbody> </table>	Item	Specification	Printing Method	Serial Impact DOT Matrix system	Printing direction	Uni-directional printing	Inking	Dedication ink ribbon cartridge (black (4+0.5)×8 Font, 40columns	Character size	[6×8, 7×10, 8×8, 8×9, 10×12]	Optional Characters	Simplified/Traditional Chinese, Arabic Persian, Latin9 and Others upon reques	Characters per line	40columns (4x8 Font)	Paper width	46.8mm, 180dots/line	Print feed pitch	3.52mm (10dot lines)		57.5mm,
Item	Specification																				
Printing Method	Serial Impact DOT Matrix system																				
Printing direction	Uni-directional printing																				
Inking	Dedication ink ribbon cartridge (black (4+0.5)×8 Font, 40columns																				
Character size	[6×8, 7×10, 8×8, 8×9, 10×12]																				
Optional Characters	Simplified/Traditional Chinese, Arabic Persian, Latin9 and Others upon reques																				
Characters per line	40columns (4x8 Font)																				
Paper width	46.8mm, 180dots/line																				
Print feed pitch	3.52mm (10dot lines)																				
	57.5mm,																				

日本keyence	Paper supplied	Ordinary paper or specified pressure s
福建新大陆	Barcode	1-dimension : Code128, EAN 128, Code39
美国双成	Black mark	2-dimension : PDF417, QR Code, DATA Ma
韩国蓝鸟bluebird	Printing speed	Support black mark detection
韩国M3	Dimensions	1.8 line/sec ± 20%
▪ 无线局域网	Weight	97 x 109 x 44.7mm
美国intermec	Interface	350g (Including battery & roll paper)
美国Symbol	Receive buffer size	UART or TTL, Bluetooth Ver2.0
▪ 不干胶标签	Battery	10K bytes
▪ 激光打印标签	Battery duration	Rechargeable 7.4V DC 1,100mAh (Li-ion)
▪ 条码碳带	AC adapter	1 hour continuous printing
IMC系列碳带	Operating temperature	Input (100~250V AC, 50~60Hz)
标准腊基碳带	Storage temperature	Output (8.4V DC / 0.8A), 4 hours full c
混合基碳带	MCBF (Mean Cycle Between	-10° C~50° C
树脂基碳带	failure)	-10° C~70° C
水洗布专用树脂碳带		Head 1.0 milli
▪ 条码打印软件		
▪ 条码检测仪		
▪ 条码打印机配件		

条码业界新闻 | 网站地图 | 条码行业动态

版权所有(C) 2002—2011 上海全亨科技

地址: 上海市浦东大道1097号15号楼4E室 邮编: 200135 邮箱: mail#i

电话: 021-51088451 51088452 传真: 021-50935062

